



OpenFlex™ Data24 NVMe-oF™ Storage Platform

The Performance of NVMe™ Flash in Shared Storage

Western Digital's OpenFlex Data24 NVMe-oF™ storage platform extends the high performance of NVMe™ flash to shared storage. It provides low-latency sharing of NVMe SSDs over a high-performance Ethernet fabric to deliver similar performance to locally attached NVMe SSDs. Unsurpassed connectivity in its class using Western Digital RapidFlex™ NVMe-oF controllers, allows up to six hosts to be attached without a switch, like a traditional JBOF.

OpenFlex Data24 NVMe-oF storage platform can also be used as a disaggregated storage resource in an open composable infrastructure environment using the OpenFlex API. OpenFlex Data24 is built to deliver high availability and enterprise-class reliability. The entire platform, including SSDs, is backed with a 5-year limited warranty.

Features

- High density and capacity
- Up to 368TB¹ in 2U
- Low latency
- Dual Port SSDs
- Bandwidth match between SSDs (Storage) and I/O (Network) – No oversubscription
- RESTful API support for simplified management
- Vertically integrated Western Digital design: NVMe SSDs, fabric adapters and platform
- Superior serviceability and high quality global support services
- Industry leading – 5 year limited warranty

Benefits

- Enables servers to share NVMe flash storage as if it were local
- Uses low latency fabric to fully utilize IOPS and capacity
- Provides more efficient use of large capacity SSDs
- High performance RapidFlex NVMe-oF controllers
- Fan out to six connections without a switch
- Balanced design to eliminate over-subscription and maintain NVMe performance
- Disaggregates NVMe shared storage for open composability
- Allows multiple hosts concurrent access at low latency
- Leverages mature standard NVM Express over Fabrics 1.0a
- Provides open composability in a 2U 24-bay platform

¹ One terabyte (TB) is equal to one trillion bytes.
Actual user capacity may be less due to operating environment.

OpenFlex™ Data24 NVMe-oF™ Storage Platform

PRODUCT BRIEF

Specifications

Hardware	Specifications	OpenFlex Data24
<ul style="list-style-type: none">• 24 Dual port high-performance SSDs	Form Factor	2U
<ul style="list-style-type: none">• Wide range of NVMe SSD capacity and endurance options<ul style="list-style-type: none">- Ultrastar® DC SN840: 1DWPD: Up to 15360 GB- Ultrastar DC SN840: 3DWPD: Up to 6400 GB	Front Drive Bays	Up to 24 x U.2 NVMe SSDs
<ul style="list-style-type: none">• High availability with dual IOM	Power Supply	2x 2000W Platinum 200–240VAC, CRPS, Hot Plug
<ul style="list-style-type: none">• 3 PCIe x 16 slots/IOM	Fabric Adapter Slots	6x PCIe x16
<ul style="list-style-type: none">• Up to six 100GbE ports with dual IOM at full performance	Fabric Adapter(s)	Western Digital RapidFlex NVMe-oF Fabric Adapter
<ul style="list-style-type: none">• Western Digital RapidFlex NVMe-oF fabric adapters	Cabling	Passive (1 – 5M) and Active Optical (5 – 50M)
<ul style="list-style-type: none">• OpenFlex inspired composability in a mainstream 2U24	Platform Management	ARM based BMC
<ul style="list-style-type: none">• 28" (711mm) chassis depth – fits most commonly used short depth racks (800 – 1000 mm)	Rear I/O	1G-BASE-T Management Port (RJ-45)
	HA Redundancy	Dual IOMs, Dual Port SSDs, Dual PSUs, Dual Rotor Hot Plug fans
	Environmental	10°C – 35°C
	Chassis Dimensions (Height x Width x Depth)	8.75 × 44.80 × 71.12 cm 3.45" x 17.64" x 28" in
	Weight	Maximum 31.75 kg / 70 lb
	Limited Warranty	5 years standard

Western Digital

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com/support

© 2020 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, OpenFlex, RapidFlex, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe and NVMe-oF word marks are trademarks of NVM Express, Inc. All other marks are the property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications and do not constitute a warranty. Actual specifications for unique part numbers may vary. Pictures shown may vary from actual products.